## WO0225420

Publication Title:

METHOD, SYSTEM AND COMPUTER PROGRAM FOR MANAGING VIEWS AT A COMPUTER DISPLAY

## Abstract:

A views management system has a computer display (14) which provides a hideable view bar having pane splitting controls (42,46,48) and a list of open views (44). Through selection of specific ones of the pane splitting controls (42,46,48), a system user can configure the display (14) to show any number and arrangement of tilled views. By simply selecting one of the open views in the list (44) appearing in the view bar, the user can assign that view to the pane currently having focus. The contents of pairs of panes can easily be swapped by a click-drag-drop operation sequence using a cursor- controlling pointing device (32).

Data supplied from the esp@cenet database - http://ep.espacenet.com

This Patent PDF Generated by Patent Fetcher(TM), a service of Patent Logistics, LLC

(19) World Intellectual Property Organization International Bureau



# 

# (10) International Publication Number WO 02/25420 A1

(43) International Publication Date 28 March 2002 (28.03.2002) (51) International Patent Classification7:

PCT

G06F 3/033

Raleigh, NC 27613 (US). KESSEN, Bethany, Lyn; 1025

- (21) International Application Number: PCT/GB01/03564
- (22) International Filing Date: 8 August 2001 (08.08.2001)
- (25) Filing Language: (26) Publication Language:
- English
- English
- (30) Priority Data: 09/665 193 18 September 2000 (18.09.2000) US
- (71) Applicant: INTERNATIONAL BUSINESS MA-CHINES CORPORATION [US/US]; New Orchard Road, Armonk, NY 10504 (US).
- (71) Applicant (for MG only): IBM UNITED KINGDOM LIMITED [GB/GB]; P.O. Box 41, North Harbour, Portsmouth, Hampshire PO6 3AU (GB).
  - (72) Inventors: MOLANDER, Mark, Edward; 301 New Rail Drive, Cary, NC 27513 (US). MOORE, Martin, Thomas; 818A Clarendon Street, Durham, NC 27705 (US). RAUCH, Thyra, Lynne; 634 North Blount Street, Raleigh, NC 27604 (US). UTHE, Robert, Thomas; 105 Goldenrod Drive, Cary, NC 27513 (US). YATES, Stanford, Louis; 12508 Waterman Drive, Raleigh, NC 27614 (US). CLINTON, James; 3161-307 Hidden Pond Drive,

Park Summit Boulevard, Apex, NC 27502 (US).

- (74) Agent: MOSS, Robert, Douglas; IBM United Kingdom Limited, Intellectual Property Law, Hursley Park, Winchester, Hampshire SO21 2JN (GB).
- (81) Designated States (national): AR, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU. CZ, DR, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KB, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, PL, PT, RO, RU, SD, SR, SG, SL SK, SL, TJ, TM, TR, TT, TZ, UA, UG, UZ, VN, YU, ZA, ZW.
- (84) Designated States (regional): ARIPO patent (GH, GM, KB, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZW), Burnsian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BR, CH, CY, DB, DK, ES, FL, FR, GB, GR, IE, IT. LU, MC, NL, PT, SR, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD,


### Published:

with international search report

entirely in electronic form (except for this front page) and available upon request from the International Bureau

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: METHOD, SYSTEM AND COMPUTER PROGRAM FOR MANAGING VIEWS AT A COMPUTER DISPLAY



(57) Abstract: A views management system has a computer display (14) which provides a hideable view bar having pane splitting controls (42,46,48) and a list of open views (44). Through selection of specific ones of the pane splitting controls (42,46,48), a system user can configure the display (14) to show any number and arrangement of tiled views. By simply selecting one of the open views in the list (44) appearing in the view bar, the user can assign that view to the pane currently having focus. The contents of pairs of panes can easily be swapped by a click-drag-drop operation sequence using a cursor- controlling pointing device (32).

15

20

25

30

35

40

#### Field of the Invention

The present invention relates to computer systems and more particularly to a method, system and program product for managing views at a computer system display.

## Background of the Invention

At one time computer systems, whether standalone or part of a network, were relatively simple, low function devices capable of executing only a single application program at any given time. Displays or consoles used to monitor system operation gave a user only a single representation or view of the system operation. As individual systems and networks became more complex, allowing multiple tasks to be performed concurrently, system users began to have a need for more than a single view of operations or tasks being performed. The straightforward approach of dedicating a console to each of the different views had obvious usability. space and cost drawbacks. Consequently, the almost universal approach has been to develop systems and monitors capable of presenting multiple views at any given time.

The two major approaches to presenting multiple views on a console are cascading and tiling of windows or panes. For purposes of this description, the two terms "windows" and "panes" can be considered to mean the same thing, namely, a view that occupies less than an entire display screen but which still shows significant portions of a particular view. Where panes are cascading, only the topmost pane is completely visible on the display screen. The remaining panes are "stacked" beneath the topmost pane, usually with only a title bar and perhaps one vertical edge being visible. A user brings any pane in the stack to the top simply by selecting the title bar or any other visible part of that pane.

Tiled views do not overlap each other but instead occupy horizontally or vertically divided panes on the display screen. Tiling permits a user to see more information about each represented view without having to perform the type of view selection steps required for cascaded. views.

Copied from 10693324 on 12/13/2005

15

20

25

30

35

40

Known tiling techniques have disadvantages, including a lack of flexibility. Some techniques limit the user to simple, fixed tiling arrangements, such as two side-by-side panes or two above-and-balow panes. A user who wants to have a number of views greater than the fixed number of panes available in such systems is out of luck. Other techniques take an all-or-nothing approach, setting up a tile for every open view. The all-or-nothing approach is satisfactory only if the number of open views is small. As the number of open views increases, the size of each tile necessarily gets smaller, reducing the amount of useful information presented to the user.

U.S. Patent 5,880,725 - Southgate attempte to overcome some of the problems of the prior art in a computer user interface in which a screen can have both overlapping and tiled window areas. If a view is to be shown in a tiled window area, that view is fitted into the available space by shrinking the view, if necessary, to a minimum allowable size. The patent discloses what can be described as a "beet fit" approach in which a view is moved into available screen space. While this approach may be more flexible in creating a displayed views, it can also end up with panes that are considerably smaller than those required by a system user.

One well-known operating system enables a user to subdivide the display ecreen into a wide variety of horizontally or vertically divided frames. While this operating system is flexible in that it allows the user to define the total number and configuration of frames needed, it is considerably less flexible as to the steps that must be performed in loading data into the various frames. To load the contents of a particular file into a particular janel, a link to the file must be established and the filename must be keyed in. This relatively numbersome process must be repeated for every single frame in the display.

Another known system uses a fixed number of panes but allows a userto change the arrangement of the panes relative to one another using a drag-and-drop operation. Because the number of panes is fixed, the system lacks desirability flexibility.

Summary of the Invention

Accordingly, according to a first aspect, the present invention provides a method of managing the appearance of viewe on a display having a working area that includes at least one view pane, said method comprising the stepe of: a) designating one of the view pane in the working area as a focus view pane; b) invoking a view bar including a set of pane splitting controls and a list of open views; c) in response to selection of one of the pane splitting controls, dividing the focus view pane into two panes, the contents of the focus view pane being assigned to a first of the two panes; and d) in response to selection of one of the open views from the list appearing in the view bar, assigning the selected view to a second of the two panes.

3

Accordingly, according to a second aspect, the present invention provides a system for managing the representation of views comprising:
a) a display having a working area including at least one view pane designated as a focus view pane;
b) a display control subsystem for generating a view bar having pane splitting controls and a list of open views;
c) pane control logic responsive to selection of one of the pane splitting controls for dividing the focus view pane into two panes in accordance with the selected pane splitting control and for assigning the contents of the focus view pane to a first of the two panes; and

 d) view control logic responsive to selection of one of the views on the list of open views for assigning the selected view to the second of the two panes.

Accordingly, according to a third aspect, the present invention provides a computer program which, when executed on a computer, causes the computer to:

 a) designate a view pane in a working area of a computer display as a focus view pane;

b) invoke a view bar on the computer display, said view bar including a set of pane splitting controls and a list of open views;

c) in response to selection of one of the pane splitting controls, divide the focus view pane into two panes, the contents of the focus view pane being assigned to a first of the two panes; and

d) in response to selection of an open view from the list appearing in the view bar, assign the selected view to a second of the two panes.

Thus, the present invention overcomes the enumerated disadvantages of the prior art and can be implemented as a method of managing the appearance of views on the display having a working area that includes at least one view pame. The display always includes at least one view pame designated as an active or focus view pame. A user who wants to increase the number of views on the display invokes a view bar which includes a set of pame-splitting controls and a list of open views. In response to

35

40

i o

15

20

25

· 30 ·

- 15

20

25

30

40 .

selection of one of the pane-splitting controls, the view pane having focus is divided into two panes and the contents of the focus view pane are assigned to a first of the two panes. The user controls the contents of the other view pane by selecting one of the open views from the list appearing in the view bar. The selected view is assigned to the other of the view panes.

Brief Description of the Drawings

A preferred embodiment of the present invention, by way of example only, may be more readily ascertained from the following detailed description when read in conjunction with the accompanying drawings wherein:

Figure 1 is a schematic representation of a workstation or computer system console at which the present invention may be implemented;

Figure 2 is a block diagram of the major components of the computer system console;

Figure 3 is an initial or default appearance of the working area of the display of the computer system console;

Figure 4 is a representation of the working area when a view bar normally hidden along the right edge of the area is unhidden or brought into view.;

Figure 5 is a representation of the working area once pane-splitting controls and a desired view are selected;

Figure 6 is a representation of the working area following the completion of pane-splitting and view selection;

. Figure 7 is a view of the working area used to illustrate how views can be swapped efficiently among existing panes;

Figure 8 is a view of the working area following  $\mathbf{a}_{_{\! 1}}\mathbf{view}$  swapping operation;

Figure 9 is a flowchart of the method steps that are performed in setting up a new viewing pane and assigning views to the original and the new pane; and WO 02/25420

10

15

20

25

.35

Δn

PCT/GB01/03564

Figure 10 is a flowchart of the method steps that are performed in carrying out a view swapping operation.

### Detailed Description of the Preferred Embodiment

A preferred embodiment of the invention will be described below, but it should be kept in mind that the present invention can be implemented in several different forms, such as in special purpose hardware or in a combination of hardware and software. A typical combination of hardware and software is a general-purpose computer system using a computer program that, once loaded and executed, causes the system to carry out method steps which will be described below. The software may be pre-loaded into the general-purpose computer system or may be separately available as a computer program product which, when loaded into a computer system, causes the system to carry out the method steps.

The term "computer program" in the present context means any expression, in any language, code, or notation, of a set of instructions intended to cause a system having information processing capability to perform a particular function either directly or after conversion to another language and/or reproduction in a different material form.

Referring to Figure 1, the present invention is a method for managing views in a computer system 10 including a system unit 12 and a monitor or display 14. A computer user may configure panes for showing individual views in the working area 16 of the display 14, assign those views to the desired panes and swap those views in a series of simple, intuitive operations.

Figure 2 illustrates the major physical components of a general-purpose computer system dapable, when programmed properly, of implementing the present invention. The computer system includes a central processing unit (CFU) subsystem 20 with a processor and supporting registers, caches and logic circuits. The computer system further includes random access memory 22, hard drive 24 and an optical drive 26, such as a CD-R, CD-RW or DVD drive. Where the invention is implemented as a computer program, it is typically made available to the system operator initially on removable magnetic or optical media for installation onto hard drive 24. Once the initial installation is complete, the program can be transferred, as needed, from hard drive 24 into random access memory 22. Alternatively, the program may be loaded into random access memory

٠,

26. The computer system further includes system input/output (I/O) adapters 28 supporting connections to standard system components such as a keyboard 30, a pointing device 32 and a video display 34. Finally, the computer system may include a network interface card 36 which provides an interface to other networked devices.

The preferred embodisent of the present invention will be described first by reference to the changes in the display appearance in the course of use of the invention and then by reference to flowcharts describing the method steps which are performed in making those changes. Referring first to Figure 3, the initial or default appearance of the display includes a single view (VIEW 1) occupying the entire working area of the display. In the default appearance, a view bar, which will be described in more detail below, is considered to be hidden along the right edge of the display. When hidden, the view bar is represented by a thin strip of pels 38, which may include glyphs or icons representing the views.

The user changes the appearance of the display's working area by invoking or calling up the view bar, preferably by moving a cursor over the strip 38. In one implementation of the invention, the view bar automatically expands or is unhidden once the presence of the cursor above strip 38 is detected. In another implementation, the view bar remains hidden until the user performs a selection operation, such as blicking one of the buttons on the cursor control device, usually a mouse.

25

30

35

10

15

20

Figure 4 shows the working area once the view bar is unhidden using one of the above-described methods. The view bar includes pane-splitting controls, specifically a first pair of buttons 46 for dividing one view pane already in the working area into two vertically spaced panes and a second pair of buttons 42 for dividing one view pane already in the working area into two horizontally spaced panes. The pane-splitting controls are effective only for the active pane, seestimes referred to as the pane having focus or the focus pane or focus view pane. In the case of Figure 4, VIEW 1 is the only pane and by default is the focus view pane.

40

view pane is to be divided horizontally or vertically. Depending on which of the two buttons in a set is pushed, the controls determine whether the newly created pane is located to the right or to the left (or above or below) the existing pane. Referring specifically to Figure 4, it can be seen that the right facing triangle in the horizontal

The pane-splitting controls determine more than whether the focus

pane-splitting control 42 is selected. As a result of this selection, a second view pane (VIEW 2) will be created in the working area to the right of the existing VIEW 1. The view originally contained in VIEW 1 remains assigned to that pane. The contents of the new view pane (VIEW 2) are selected by the system user from a list 44 of open views in the view bar. Pigure 6 shows the working area of the display as it would appear following the cursor emphasis of a particular view, VIEW 2, for the newly created pane.

7

Figure 6 shows the working area with VIEWS 1 and 2 being located in side-by-side relationship. In Figure 6, the view bar has returned to its hidden state. The hidding of the view bar can be made to occur automatically when the cursor is moved off the view bar area or, depending upon the objectives of the system implementers, may be made not to occur until the user performs some sort of active deselection operation, such as clicking one of the buttons on the cursor control device. Note that Pigure 6 shows that VIEW 2 is automatically selected as the focus pane bocause it is believed likely that the system user who set up the pane for VIEW 2 probably did so because of an immediate need to work with that view. Making VIEW 1 the focus view can, if the user wants, be simply done by clicking on the title bar for that view.

While only two panes are shown in Figure 6, the user has the option of creating any number of additional views. For example, assuming VIEW 2 remains the focus pane, the user could opt to divide that pane into two smaller vertically-spaced panes by using the vertical pane splitting control and them selecting one of the open views in the viewbar list for the resulting unoccupied pane. The process can be repeated any number of times beginning with whichever pane has focus with obvious limitation that, as panes become smaller, they can present less information to the user. The pane splitting controls make at easy for the user to establish any desired screen configuration. The view list visible in the view bar makes it easy for the user to assign a particular view to any unoccupied pane.

If a user, having created a tiled arrangement of views, decides that the arrangement isn't what he or she wanted, the present invention makes it simple for the user to rearrange the views without altering the pane configuration. Referring to Figure 7, VIEW 1 is assigned to a large pane while VIEW 2 and VIEW 3 are each assigned to a smaller pane. If a user decides that VIEW 2 should be assigned to the larger pane, the views can

be swapped using a click-drag-drop operation. The cursor is positioned

35

10

15

20

25

30

15

20

25

30

35

40

over one of the views to be swapped and one of the device buttons is pressed and then held down as the cursor is moved to a position anywhere in the other of the two panes to be swapped. The release of the device button swaps the two views. Figure 8 shows the end result with VIEW 2 now appearing in the larger pane with VIEW 1 appearing in the lower left pane on the screen.

while the drawing shows the panes involved in the swap as being contiguous, this is not a requirement of the invention. The two panes involved in a swap may be completely separated from one another by one or more intervening panes. The views that are swapped are determined solely by the cursor position when the device button is first pressed and the cursor position when the device button is subsequently released.

Reforring back momentarily to Figure 4, the view bar is shown having two additional controls 49 and 48 not previously discussed. As noted earlier, the system may be implemented so that the view bar is hidden (disappears) automatically if the user moves the cursor away from the view bar area. Under some conditions, the user may not want the view bar to disappear automatically. Control 49 is a "pin" control which, when selected, will lock the view bar into its visible state regardless of the current position of the cursor. Once the view bar has been locked into a visible state, it cannot be hidden until some positive action is taken to reset the pin control. Examples of suitable positive actions would be clicking the pin control again and the like. Control 48 is a detach control which, when activated, causes the selected view to be 'torn off' or removed from the current pane and launched into its own separate detached window, which may be moved independently of the other tiled panes.

Figure 9 is a flow chart of sethod steps that are performed during the process of setting up a tiled screen configuration and assigning views to each of the panes in that configuration. The initial step of 50 in the process is the generation of the default display which consists of a single view having focus and the thin strip of pels representing the hidden view bar. After the default display is generated, the system monitors the position of the cursor in step 52. Once the cursor is detected as being above the hidden view bar, the view bar is revealed or unhidden in step 54 and the system waits for one of the pane splitting controls to be selected. Once step 56 detects that one of the pane splitting controls has been selected, the video buffers for the display are set up for two different panes occupying the space originally allocated to the focus pane. Whether the new panes are oriented

15

20

25

side-by-side or above-and-below one another depends, of course, on which of the pane splitting controls was selected.

In step 60 the data included in the view in the current focus pane is assigned to one of two video buffers. Again, the assignment depends on which of the pane splitting controls was selected in setting up the two new panes. The system then enters a wait state, during which it monitors the state and condition of the cursor to determine whether one of the open views in the list of views appearing in the view bar has been selected. Once selection of an open view is detected in step 62, the data for the selected view is loaded, in step 64, into the second of the two newly created panes. As noted earlier, it is entirely within the discretion of the system user how many times to run this process in order to achieve a tiled configuration of the display working area that he or she is satisfied with.

Figure 10 is a flow chart of steps that are performed in carrying out the previously-discussed visw swapping operation. The initial step 70 of the process is to destermine whether a particular key or button has been depressed while the cursor is located above one of the existing panes. Once the key or button depression is detected, the system then begins monitoring the state of the cursor to determine whether the same key or button is subsequently released after the cursor has moved to a position above another of the existing panes. If a test 72 shows that the key has been released over a second pane, the data representing the two affected views is swapped between the first and second panes.

15

20

30

#### CLAIMS

- A method of managing the appearance of views on a display having a working area that includes at least one view pane, said method comprising the steps of:
  - a) designating one of the view panes in the working area as a focus view pane;
- b) invoking a view bar including a set of pane splitting controls and a list of open views;
  - c) in response to selection of one of the pane splitting controls, dividing the focus view pane into two panes, the contents of the focus view pane being assigned to a first of the two panes; and
  - d) in response to selection of one of the open views from the list appearing in the view bar, assigning the selected view to a second of the two panes.
  - A method as claimed in claim 1 wherein the view bar is normally hidden from view at one edge of the working area and wherein the step of invoking the view bar is responsive to moving a cursor into a position coincident with said edge of the working area.
    - A method as claimed in claim 2 including the additional step of, in response to user input, pinning the view bar into a displayed state.
    - 4. A method as claimed in any preceding claim including the additional step of, in response to the user, selecting one of the view panes in the working area, and dragging the contents of the selected view pane to another of the view panes in the working area, swapping the contents of the selected view pane with said another view pane.
- 35 5. A system for managing the representation of views comprising:
  - a) a display having a working area including at least one view pane designated as a focus view pane;
- b) a display control subsystem for generating a view bar having pane splitting controls and a list of open views;

15

20

25

- c) pane control logic responsive to selection of one of the pane splitting controls for dividing the focus view pane into two panes in accordance with the selected pane splitting control and for assigning the contents of the focus view pane to a first of the two panes; and
- d) view control logic responsive to selection of one of the views on the list of open views for assigning the selected view to the second of the two panes.

6. A system as claimed in claim 5 wherein the view bar is normally hidden and said display control subsystem responds to the presence of a display cursor in a predetermined region of the display to unhide the view bar.

- 7. A system as claimed in claim 6 wherein the display control subsystem further includes logic for maintaining the appearance of the view bar.
  - 6. A system as claimed in any of claims 5 to 7 wherein the display control subsystem further includes logic for altering the appearance of the vorking area, said logic including view swapping logic for swapping the contents of two selected view panes in the working area.
    - 9. A computer program which, when executed on a computer, causes the computer to:
      - a) designate a view pane in a working area of a computer display as a focus view pane;
      - invoke a view bar on the computer display, said view bar.
         including a set of pane splitting controls and a list of open views;
      - c) in response to selection of one of the pane splitting controls, divide the focus view pane into two panes, the contents of the focus view pane being assigned to a first of the two panes; and
      - d) in response to selection of an open view from the list appearing in the view bar, assign the selected view to a second of the two panes.
- 40 10. A computer program as claimed in claim 9 wherein the view bar is normally hidden from view at one edge of the working area and said program

product responds to the presence of a cursor in a predetermined area at said edge to unhide the view bar.

- A computer program as claimed in claim 10 wherein said program
  product responds to a user input to pin the view bar into its displayed
  state.
- 12. A computer program as claimed in any of claims 9 to 11 which responds to selection of one of the view panes in the working area and dragging of the contents of the selected pane over another view pane to swan the contents of the two panes.







Fig. 1










Fig. 5




Fig. 6




Fig. 7





Fig. 8






Fig. 10

# INTERNATIONAL SEARCH REPORT

PC1/6R 01/03564

4 01 1 00				
ÎPC 7	IFICATION OF SUBJECT MATTER G06F3/033			
	o international Patent Classification (IPC) or to both national classification	ication and IPC		
	SEARCHED ocumentation searched (dassification system followed by classification system followed by classific			
IPC /	606F			
	tion searched other than minimum documentation to the extent that			
Electronic d	fala base consulted during the international search (name of data b	ese and, where practical, search terms	used)	
EPO-In	ternal, WPI Data, PAJ, IBM-TDB, INS	PEC		
C. DOCUM	ENTS CONSIDERED TO BE RELEVANT	· · · · · · · · · · · · · · · · · · ·		
Category *	Challen of document, with indication, where appropriate, of the n	blevant passages	Relevant to claim No.	
Α	US 6 104 401 A (PARSONS PAIGE K) 15 August 2000 (2000-08-15) column 7, line 60 -column 8, line 30		1,5,9	
A	WO 94 24657 A (APPLE COMPUTER) 27 October 1994 (1994-10-27) page 2, line 10 - line 15; claim	1,5,9		
A	WO 99 10799 A (HUGH HARLAN M ;NA LLC (US)) 4 March 1999 (1999-03- page 10, line 21 -page 11, line figures	1,5,9		
		- <b>/-</b> -		
X Furth	her documents are listed in the continuation of box C.	Patent family members are it	sted in annex.	
**E can'ter document but published on or after the hierardonal filing data,  **U document which may threw doubte on priving; claiming) or  **U document which may threw doubte on priving; claiming) or  **Claiming of other specified reasons in a specified; of another  **Claiming of other specified reasons in a specified;  **O' document miniming to an oral disclosurer, use, exhibition or  **other maters  **P' document published prive to the international filing data but  sinter that the publy date citation  **International filing data but  sinter that the publy date citation  **Other maters  **Other ma		The birth document published after the International Ring data child to indivisite the principle or bandy underlying the Invention International the principle or bandy underlying the Invention International Internation Internation International Internati		
Date of the o	actual completion of the International search	Date of mailing of the international	search report	
	9 December 2001	02/01/2002		
Name and m	ualing addruss of the ISA European Palent Office, P.B. 5618 Patentisan 2 NL – 2280 HV Rigweyt Tel. (431–70) 340–2000, Tx 31 651 epo nl, Fac: (431–70) 340–3016	Authorized officer Durand, J	· · · · · · · · · · · · · · · · · · ·	

# INTERNATIONAL SEARCH REPORT

Inter nat Application No PC1/6B 01/03564

C.(Continu	milon) DOCUMENTS CONSIDERED TO BE RELEVANT	7C1/65 UI	, ,,,,,,,
	Citation of document, with indication, where appropriate, of the relovant passages		Relevant to claim No.
A	PATENT ABSTRACTS OF JAPAN vol. 1998, no. 14, 31 December 1998 (1998-12-31) å JF 10 254674 A (SAMSINNS ELECTRON CO LTD), 25 September 1998 (1998-09-25) abstract; figures å EP 0 863 457 A 9 September 1998 (1998-09-09)	1,5,9	
		÷	
			(4)
	*		

## INTERNATIONAL SEARCH REPORT

emation on patent family members

Inter not Application No PC1/bB 01/03564

					db 01/03504
Patent document cited in search report		Publication date		Patent family member(s)	· Publication date
US 6104401	Α	15-08-2000	US	6025844 A	15-02-2000
WO 9424657	A	27-10-1994	AU	· 6707394 A	08-11-1994
			CA	2161023 A1	27-10-1994
			DE	69428988 D1	13-12-2001
			EP	0695448 A1	07-02-1996
			JP	8509311 T	01-10-1996
			WO	9424657 A1	27-10-1994
			US	5714971 A	03-02-1998
WO 9910799	A	04-03-1999	US	6166736 A	26-12-2000
			AU	8917798 A	16-03-1999
			EP	1015961 A1	05-07-2000
			MO	9910799 A1	04-03-1999
JP 10254674	A	25-09-1998	EP	0863457 A2	09-09-1998

Form PCTASA/210 (peters termily ervnex) Likely 199

# This Page is Inserted by IFW Indexing and Scanning Operations and is not part of the Official Record

# BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

☐ BLACK BORDERS
$\square$ image cut off at top, bottom or sides
A FADED TEXT OR DRAWING
D BLURRED OR ILLEGIBLE TEXT OR DRAWING
☐ SKEWED/SLANTED IMAGES
☐ COLOR OR BLACK AND WHITE PHOTOGRAPHS
☐ GRAY SCALE DOCUMENTS
$\square$ lines or marks on original document
$\square$ reference(s) or exhibit(s) submitted are poor quality
OTHER:

# IMAGES ARE BEST AVAILABLE COPY.

As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.